

SHOP NOW >

Project Name: Type: Quantity:

## **FIXTURE SPECIFICATIONS**

## **INTENDED USE**

Our aluminum remote-controlled RGBW color-changing LI light features a clear glass lens to maximize light and prote from environmental hazards. Designed to provide even an bright illumination across wide areas for shopping mall, he and landscaped exteriors, this is an innovative solution for residential as well as commercial color-changing application.

# 

# **DETAILS**

**Dia** 3.74" x **H** 5.50"

Construction: Aluminum Housing, Stainless Steel Cover, P

Sleeve

Lens: Clear glass lens

Wiring: 5" SJTW 20AWG Lead Wire Color Temperature: RGBW + 3000K

Lumen: 620 Lumens

**Voltage:** 12VAC/DC. Voltage Drop may occur at distances greater

than 20 Feet.

Wattage: 10W

Beam Spread: 90°

Life: 50,000 Hours

**Operating Temperature:** -20°F ~ 110°F


**Traffic Rated:** Drive-over rated for normal passenger vehicles 5.50"

**Remote Control:** IR remote control with on and off switch.

Wireless IR Remote can control multiple lights from 10 feet away.

**Life:** 50,000 Hours

**Listing:** Wet-location rated, IP67









Ordering Information: Example: (9033-WC)

Model

**Options** 

**9033 WC** Wireless Controller



12-24 VDC Wireless Controller. Supports 192W Max.



# 12V WATERPROOF ELECTRONIC LED DRIVER

# **SPECIFICATIONS**

Input Voltage: 90~145VAC

Input AMP: 3.2A Max.
Output Voltage: 12VDC
Output AMP: 16.5A Max.

Wattage: 200W Max.

**Dimming:** Non-Dimmable driver

**IP Rating:** IP67 Outdoor Use 3ft. Power cable

Two 8" Output Low-Voltage Cables

