

FIXTURE SPECIFICATIONS

INTENDED USE

Our in-ground product is ideal for outdoor well lighting. This light delivers superior design, optimal functionality and consistent quality in warm white, 3,000-Kelvin lighting. Assembled to order, the product comes with 120-volt line voltage, making the Trento well light perfect for either residential or commercial use

FEATURES

Construction: Fiberglass reinforced bronze composite with molded brass inserts for screws

Adjustably: 30° Adjustable

Voltage: 120V

(Supplied with Built-In 25W Magnetic Low Voltage Transformer)

Color Temperature: 3000K

CRI: 80

Life: 50,000 Hours

Warranty: 3 Years for Composite (Cosmetic Defects)

Limited Life-Time for Aluminum & Brass (Cosmetic Defects)

5 Years Carefree for LED Component (Labor Not Included)


Listings: cETLus, IP65




Shown with Curved Wall Wash Reflector




Shown with Grill Lens Shield



No Shield



Grill



Curved Wall Wash Reflector



ORDERING INFORMATION Example: (9038-A-BK-7W-B15-C)

Model	Material	Finish	Wattage & Lumen	Beam Spread	Lens	Shield	Options
9038	A	BK	7W	B15	C	(Blank)	CPS
	Aluminum	Black	7W 450lms	15° Spot	Convex	No Shield	Concrete
	B	BR	11W	B40	Non-Tempered	GR	Pour Sleeve
	Brass	Bronze	11W 600lms	40° Narrow Flood	F	Grill	
	C	WH	15W	B60	Flat Stepped	WW	
Composite	White	15W 900lms	60° Flood	Tempered Reflector	Curved Wall Wash Reflector		
		CR	20W	B160			
		Chrome	20W 1500lms	160° Wide Flood			
		AG					
		Antique Green					
		UB ¹					
		Unfinished Brass					

¹ Only Available for Brass Material

PHOTOMETRICS

