

**\*\*\*PLEASE SAVE THESE IMPORTANT SAFETY INSTRUCTIONS\*\*\***

**This Product Must Be Installed in Accordance with the Applicable Installation Code by a Person Familiar with the Construction and Operation of the Product and the Hazards Involved/**

**Ce Produit doit être Installé selon le Code D'Installation pertinent, par une Personne qui connaît bien le Produit et son Fonctionnement ainsi que les Risques Inhérents.**

**Installation recommended to be done by a professional electrician and must be in accordance with local codes of the National Electrical Code (NEC)**

**TOOLS REQUIRED FOR INSTALLATION:**

**Wire Strippers, Flathead Screwdriver, Philips Screwdriver**

1. To prevent electrical shock, disconnect before installation or service.
2. Strip the two (2) leads from the fixture wire. Using a silicone filled connector or outdoor rated wire nuts (**not supplied**) connect the leads from the fixture to the main supply cable leads.  
**NOTE: Wire shall not be buried more than 6 inches below surface. Secure connection to the main supply cable. Always coil extra wire not used below fixture for future relocation if desired.**
3. Adjust fixture to desired angle.  
**NOTE: When no escape outlet is provided avoid aiming fixture directly upward. When possible, set at angle to prevent rain or irrigation water from setting on lens. This is not applicable in the Well Light Series.**
4. Reconnect power after servicing.

**WARNING: TO REDUCE THE RISK OF FIRE OR INJURY TO PERSONS:**

1. To prevent electrical shock, disconnect power supply before servicing.
2. Do not touch lens, guard, or enclosures. Allow fixture to cool down before servicing.
3. Do not operate fixture with missing or damaged parts.

**LAMP INSTALLATION / REPLACEMENT:**

**CAUTION: DO NOT EXCEED MAXIMUM WATTAGE MARKED ON FIXTURE LABEL.**

1. Lamp gets **HOT** quickly! Do not touch lighted lamp, lens, guard, or enclosures. Lighted lamp is **HOT!** Please allow fixture to cool down before servicing. Please keep lamp away from **combustible materials that may burn**. Contact only switch/plug when turning on. To prevent electrical shock, disconnect power supply before replacing lamp.
2. Remove shroud to expose lamp.
3. Replace lamp with correct wattage and type of lamp marked on fixture label.  
**NOTE: DO NOT touch Halogen Lamp with bare hands. Always use the plastic bag (if available) or soft cloth when handling the lamp. Oil from skin may damage lamp.**
4. Re-install shroud.
5. Reconnect power.