

FIXTURE SPECIFICATIONS

INTENDED USE

Add maximize light output with this stainless steel in-ground well light. Featuring a tempered glass lens and grill to protect from natural hazards, our light applies to most locations, soil and concrete. Also available with RGBW color tuning technology.

DETAILS

D 10.25" x **W** 10.25" x **H** 14.38"

Construction: Stainless Steel w/ PVC Sleeve **Installation:** Rated for In-Ground Soil and

Concrete Applications

Lens: Clear, Heat Resistant, Tempered Glass


ADDITIONAL FEATURES

D94I 5a fda $^{\prime\prime}$ Wd, 4^{\prime} g WfaafZ h[S E_ Sd >[XV/Ž E_ Sd >[h[Y_ aT[$^{\prime\prime}$ Sbb /ShS[$^{\prime}$ ST $^{\prime\prime}$ Wad[A E


S`V3`Vda[VVVM[UVefi**CRI:**80+

Life: 35,000 Hours

Listing: ETL Approved for Wet Location **Lamp Type:** PAR38 LED Included



















ORDERING INFORMATION Example: (9095-RGBW)

| Model | | Lamp Type | | Color Temp | |
|-------|--------------|--|--------------------------|----------------------------------|--|
| 9095 | RGBW | RGBW 15W 1300 lms 120° Beam Spread 120V | (Blank) | RGB + W (27-64K) | |
| | W-25 W-40 | White 12.5W 1200 lms 25° Beam Spread 120-277V White 12.5W 1200 lms 40° Beam Spread 120-277V | 27K 30K 40K 50K | 2700K 3000K 4000K 5000K | |