

INSTALLATION INSTRUCTIONS

Installation recommended to be done by a professional electrician and must be in accordance with local codes of the National Electrical Code (NEC)

WARNING: TO REDUCE THE RISK OF FIRE OR INJURY TO PERSONS:

1. To prevent electrical shock, disconnect power supply before servicing.
2. Do not touch lens, guard or enclosures. Allow fixture to cool down before servicing.
3. Do not operate fixture with missing or damaged parts.

Installation

1. To prevent electrical shock, disconnect power supply before installation.
2. Remove lens cover screws.
3. Pull wires through housing.
4. Install and fix housing to suitable wall location.
5. Connect wire according to color code (White on White, Black on Black).
6. Assure that connections are correct for watertight seal.
7. Replace reflector and socket bracket.
8. Install lamp with correct wattage and type of lamp marked on fixture label.
9. Re-install Lens cover.
10. Assure proper placement of Gasket and Lens for watertight seal.
11. Reconnect power supply.

LAMP INSTALLATION/ REPLACEMENT:

***CAUTION: DO NOT EXCEED MAXIMUM WATTAGE MARKED ON
FIXTURE LABEL.***

1. To prevent electrical shock, disconnect power supply before replacing lamp.
2. Remove lens cover to expose lamp.
3. Replace lamp with correct wattage and type of lamp marked on fixture label.
4. Re-install Lens cover.
5. Reconnect power.