

Project Name:

Type:

Quantity:

Shop Now


FIXTURE SPECIFICATIONS

INTENDED USE

The specifications grade Deep Dome Architectural LED High Bay Direct Down Light Fixture has been designed to offer high light output and withstand harsh industrial conditions. The Deep Dome provides high CRI increasing the light quality of a space and improving visibility, thus reducing the chance of accidents.

AVAILABLE SIZES

Dia 8" x H 7.25" Dia 10" x H 9.25" Dia 12" x H 12.25" Dia 16" x H 14.25" Dia 20" x H 18.25"



FEATURES

Construction: Sleek Design with Large Reflective Surface for Smooth Down Lit Glow

Voltage: 120V/277V Dimming: 0-10V

CRI: 75

Life: 50,000 Hours

Warranty: 1 Year carefree for parts & components (Labor not included)

Listings: ETL Listed













ORDERING INFORMATION Example: (15201-8-15W-30K-WH-WH-48ACB)

Model	Size		Wattage Lumens	Color Temp		Exterior Finish		Interior Finish		Mounting	
15201	8 10 12 16 20	8" 10" 12" 16" 20"	15W 15 Watts 1650 lms 20W ¹ 20 Watts 2400 lms 30W ¹ 30 Watts 3600 lms 40W ¹ 40 Watts 4800 lms	30K 40K 60K ²	3000K 4000K 6000K	WH BK RD BL GR YL GV CP SN	White Black Red Blue Green Yellow Galvanized Copper Satin Nickel	WH BK RD BL GR YL GV ³ CP SN	White Black Red Blue Green Yellow Galvanized Copper Satin Nickel	48ACB 48ACW ST12 ST18 ST24 ST36 ST48	48" Black Finish Cord 48" White Finish Cord 12" L x 1/2" Stem 18" L x 1/2" Stem 24" L x 1/2" Stem 36" L x 1/2" Stem 48" L x 1/2" Stem

¹ Only Available in 30K & 40K 2 Only Available with 15W 3 Only Available with Galvanized Exterior Finish