Quantity:



Project Name:

Type:

FIXTURE SPECIFICATIONS

INTENDED USE

The specification grade **Alcon Lighting Architectural 2x2 and 2x4 LED Parabolic Lens Troffer** deliver continuous clean lines and clear light to commercial, hospitality and residential interior architectural lighting applications. Our modern, slim profiles and stylish LED Lights offer excellent direct lighting, exceptional performance and versatility for office lighting as well as classrooms, conference rooms, museums, retail outlets, hotels, restaurants, and more. The Commercial LED Lighting integrated LED Troffer Lights are available in standard lengths of 2x2 and 2x4.

AVAILABLE SIZES

2x2 | W 23.75" x L 24" x D 5.5" 2x4 | W 23.75" x L 48" x D 5.5"

FEATURES

Construction: Die-Formed and embossed code 22 gage steel. Louvers are formed in aluminum.

Mounting: Recessed inverted T-Bar ceilings. Grid mount.

Finish: High reflectance baked white enamel, with black reveal support

rails Installation: Wiring knockouts are provided on

back and end of housing. Ballast cover or reflector snaps into place; no

tools required for ballast access.

Voltage: 120-277V (50/60 Hz) Constant Current


Dimming: 0-10V

CRI: 80+

Life: 50,000 Hours

Warranty: 5 Years Carefree for Parts & Components (Labor Not Included)

Listings: cULus Listed, Suitable for Damp Locations



23.75"



ORDERING INFORMATION Example: (14015-22-30-9C-30K)

l Model	Size	 Wattage Lumens	 # of Louver Cells & Material	Color Temperature	Options
14015	22 2x2	30 Watts, 2600 lms 42 42 Watts, 3300 lms 48 48 Watts, 4500 lms	9C 9 Cells (3x3), Semi-Specular, 3" Nominal 12C 12 Cells (3x4), Semi-Specular, 3" Nominal 16C 16 Cells (4x4), Semi-Specular, 3" Nominal 9C 9 Cells (3x3), Full-Specular, 3" Nominal 16C 16 Cells (4x4), Full-Specular, 3" Nominal 9C 9 Cells (3x3), White, 3" Nominal 16C 16 Cells (4x4), White, 3" Nominal	30K 3000K 35K 3500K 40K 4000K 50K 5000K	WP 6FT Whip, 3/18ga WP10 6FT Whip, 4/18ga EM12 12W Remote Emergency Batte Backup EM20 20W Remote Emergency Batte Backup
	24 2x4	60 60 Watts, 5000 lms 85 85 Watts, 7400 lms	12C 12 Cell (2x6) Semi-Specular, 3" Nominal 16C 16 Cell (2x8) Semi-Specular, 3" Nominal 18C 18 Cell (3x6) Semi-Specular, 3" Nominal 32C 32 Cell (4x8) Semi-Specular, 3" Nominal 24C 24 Cell (4x6) Semi-Specular, 3" Nominal 18F 18 Cell (3x6) Full-Specular, 3" Nominal 32F 32 Cell (4x8) Full-Specular, 3" Nominal 18W 18 Cell (3x6) White, 4" Nominal 32W 32 Cell (4x8) White, 4" Nominal		