

FEATURES & SPECIFICATIONS

INTENDED USE

Allows standard troffers, recessed indirect/direct, or parabolics to be mounted in drywall, plaster or wood ceilings. Designed to be used with any grid type recessed luminaire in ceiling requiring flanges. May be nailed to framing for purpose of trimming out the ceiling opening not to be used for support of luminaire.

If this method

of installing frame-in-kit is used luminaire must be supported by #12 ga. mild steel wire by others.

SIZE

1 x 4 - Ceiling Opening 12.25" x 48.25"

2 x 2 - Ceiling Opening 24.25" x 24.25"

2 x 4 - Ceiling Opening 24.25" x 48.25"

ADDITIONAL FEATURES

- Die-formed and embossed code 22 gauge steel. No tools required.
- Mounting: Recessed inverted T-Bar ceilings. Grid mount.
- Fixture and Ballast: UL Listed.
- Ballast: Thermally protected, class P, HPF, Non PCB.

INSTALLATION

All dimensions are inches. Specifications subject to change without notice.

1. Slide (Snap-Lock) Corner angles into side and end/Intermediate Rails as shown.

2. Place assembled frame into ceiling opening and wire support (at four corners as shown) from main floor/ceiling structure.

WARNING: ELECTRICAL SHOCK POTENTIAL!! Do not attempt to install, maintain or relamp without disconnecting all power. Failure to disconnect power can result in electrocution, shock, or severe burns.

