


FEATURES & SPECIFICATIONS

INTENDED USE

Architectural linear fluorescent suspension lighting fixtures bring clean lines and clear light to commercial or residential office lighting interiors. Our sleek, stylish fixtures offer highly effective and efficient lighting solutions for hotels, offices, retail outlets, restaurants, and more.

SIZE

4 ft. - W 5.75" x L 48" x H 6"
 8 ft. - W 5.75" x L 96" x H 6"



ADDITIONAL FEATURES

- Matte White Lens come standard
- UD Light Distribution: Up light 12% Down Light 88%
- Lamp Type: 54 Watt T5HO
- Electronic Multivolt (120-277V)

Listings:



Ordering Information:

Example: (10120-4-UD-WH-AC60WH)

Model	Length/Distribution/ # of Lamps	Finish	Suspension Length	Options
10120	4-U 4 Ft. Uplight 1 Lamp 4-D 4 Ft. Downlight 1 Lamp 4-UD 4 Ft. Up/ Downlight 2 Lamp 8-U 8 Ft. Uplight 2 Lamp 8-D 8 Ft. Downlight 2 Lamp 8-UD 8 Ft. Up/ Downlight 4 Lamp	WH White BK Black SI Silver BZ Bronze RD Red	AC60WH 60" Adjustable Aircraft Cable (x2); 0.4" Thick 5-Conductor Power Cable (x1); 5" Round White Canopy (x2) AC60BK 60" Adjustable Aircraft Cable (x2); 0.4" Thick 5-Conductor Power Cable (x1); 5" Round Black Canopy (x2) AC180WH 180" Adjustable Aircraft Cable (x2); 0.4" Thick 5-Conductor Power Cable (x1); 5" Round White Canopy (x2) AC180BK 180" Adjustable Aircraft Cable (x2); 0.4" Thick 5-Conductor Power Cable (x1); 5" Round Black Canopy (x2) ST24WH 24" Stem (x2); 0.4" Thick 5-Conductor Power Cable (x1); 5" Round White Canopy (x2) ST24BK 24" Stem (x2); 0.4" Thick 5-Conductor Power Cable (x1); 5" Round Black Canopy (x2)	EM14 Emergency Ballast, 1400 lum AB Dual Circuit AB Switching CRWK Continuous Row Wiring Kit

Beam Series 10120 Fluorescent Suspended Pendant Light Strip - Direct / Indirect