5.5"






FEATURES & SPECIFICATIONS

INTENDED USE

The Alcon Lighting **Elite** Architectural LED Center Basket Troffer is designed to reflect light from its matte surface to provide a glare-free, softened "sky light" appearance where abundant and comfortable lighting is needed. The Elite series is configured for recessed applications in commercial and industrial buildings and is ideal for schools and offices.



DETAILS

W 23.94" x **L** 23.75" x **H** 5.5"

Construction: Die-formed, cold-rolled heavy gauge

steel housing Corrosion Resistant

Diffuser: Perforated metal diffuser with white acrylic

Mounting: Recessed mount in expose T-Bar ceilings



Voltage: 120-277

CRI: 80+

Dimming: 0-10V 100%~10% Life: L70 - 50,000 Hours

Operating Temperature: -4°F ~ 122°F

Power Factor: +0.9 Efficiency: +85%


THD: <20


Listing: Suitable for damp locations

ARRA Compliant









Ordering Information:

Example: (14001-36W-50K)

| Model | Wattage/Lumens | | Color Temp | | Options | |
|-------|----------------|--------------------|------------|-------|---------|-----------------------------------|
| 14001 | 27W | 27 watts, 1727 lms | 30K | 3000K | OS | Occupancy Sensor |
| | 36W | 36 watts, 2133 lms | 35K | 3500K | DPL | Dust/Bug Proof Clear Acrylic Lens |
| | 44W | 44 watts, 2235 lms | 40K | 4000K | EM5 | 5W Emergency Ballast |
| | | | 50K | 5000K | EM8 | 8W Emergency Ballast |
| | | | | | EM16 | 16W Emergency Ballast |