

FEATURES & SPECIFICATIONS

INTENDED USE

The **Alcon Lighting Planor Series Recessed LED Architectural Linear Lighting** fixtures bring clean lines and clear light to commercial LED or residential office lighting interiors. Our sleek, stylish fixtures offer highly effective and efficient lighting solutions for hotels, offices, retail outlets, restaurants, and more.

DETAILS

4 FT - W 6" x L 48" x H 6"

Construction: Die-formed housing and welded of heavy gauge cold rolled steel

Lens: Snap In Frosted Acrylic

ADDITIONAL FEATURES

Type: Wall Wash

Voltage: 120-277

Dimmable: 0-10V

Life: 50,000 Hours

Listings: ETL Listed for LED Components Only



Recessed/
Wall Wash



Ordering Information:

Example: (14101-4-RWW-R-R24-35K-EM)

Model	Mounting	Wattage and Lumens	Color Temp	Dimming	Flange Finish
14101-4-RWW Recessed Wall Wash	R Trimless 1" T-Bar Grid Ceiling ¹	R24 24 watts, 2400 lumens	27K 2700K (+90 CRI)	DM10 0-10V Dimming 100%-10% (Title 24 Compliant)	(Required for RF only) WH White
	RR1/2 Trimless 1/2" Drywall Hard Ceiling ¹	R48 48 watts, 4800 lumens	35K 3500K (83 CRI)	DM1 0-10V Dimming 100%-1% (Title 24 Compliant)	BK Black
	RR5/8 Trimless 5/8" Drywall Hard Ceiling ¹		40K 4000K (83 CRI)		SL Silver
	RRXX Trimless Custom Drywall Hard Ceiling ¹		50K 5000K (83 CRI)		
	RF Flanged Drywall Hard Ceiling				

Options



EM
Emergency Ballast

CRWK
Continuous Row
Wiring Kit

DS
Daylight Sensor

¹Trimless mounting options do not require finish