

Project Name:

Type:

Quantity:

FIXTURE SPECIFICATIONS

INTENDED USE

The specification-grade Reyon Architectural Low Profile LED Suspension Lighting delivers continuous clean lines and clear light to commercial, hospitality and residential interior lighting applications. Our modern, slim profiles and stylish designs offer excellent illumination, exceptional performance and versatility in offices, classrooms, conference rooms, museums, retail outlets, hotels, restaurants, and more. The integrated LED Reyon is available in standard lengths of 4', and 8', and can be joined together in seamless runs of any length.

AVAILABLE LENGTHS

4FT | W 10.8" x L 48" x H 3.5"
8FT | W 10.8" x L 96" x H 3.5"
XFT | Continuous Run Consult Factory

FEATURES

Construction: Rugged steel housing; powder-coated anti-rust protection

Continuous Row: Full ability to tandem mount for continuous run application equipped with male & female quick connect harnesses

Dimming: 5-wire 0-10V (100%-10%), cable kit with 5 wires power feed; + 0.4" 5-conductor cable + 5" round canopy

Voltage: 120-277V

Power Factor: > .95

THD: < 20

Life: 50,000 hours L70

Operating Temperature: -4°F (-20°C) - 122°F (50°C)

Warranty: 5 years carefree for parts & components (labor not included)

Listings: CA Title 24 Compliant, cETL Listed, LED chips tested to LM-80 standards



ORDERING INFORMATION Example: (12124-4-D48-MW-30K-WH-AC48-EM)

Model	Size Wattage Lumens	Lens	Color Temp	Finish	Mounting	Options
12124	4 Foot (48")					
	4-D48 Down: 48 watts 5650 Lumens	FR Frosted White Std	30K 3000K	WH White Std	AC48 Std	EM
	4-D57 Down: 57 watts 6400 Lumens	PL ² Parabolic Louver	35K 3500K	BK Black	48" Adjustable Cable	Emergency Battery Backup Remote
	4-D24U12 ¹ Down: 24 watts Up: 12 watts 3600 Lumens		40K 4000K	RD Red	AC96	
	4-D32U16 ¹ Down: 32 watts Up: 16 watts 6470 Lumens		50K 5000K	IN Iron	96" Adjustable Cable	
				SL Silver		
	8 Foot (96")					
	8-D97 Down: 97 watts 11300 Lumens					
	8-D114 Down: 114 watts 12800 Lumens					
	8-D48U24 ¹ Down: 48 watts Up: 24 watts 9580 Lumens					
	8-D64U32 ¹ Down: 64 watts Up: 32 watts 12940 Lumens					

¹ Not available with PL Parabolic Louver

² Not available with Uplight

