

**Project Name:** 

Type:

Quantity:

**SHOP NOW** 

## **FIXTURE SPECIFICATIONS**

## **INTENDED USE**

The specification-grade Reyon Architectural Low Profile LED Suspension Lighting delivers continuous clean lines and clear light to commercial, hospitality and residential interior lighting applications. Our modern, slim profiles and stylish designs offer excellent illumination, exceptional performance and versatility in offices, classrooms, conference rooms, museums, retail outlets, hotels, restaurants, and more. The integrated LED Reyon is available in standard lengths of 4', and 8', and can be

**W** 10.8" x **L** 48" x **H** 3.5" **W** 10.8" x **L** 96" x **H** 3.5"

XFT | Continuous Run Consult Factory



Construction: Rugged steel housing; powder-coated anti-rust protection with frosted

Continuous Row: Full ability to tandem mount for continuous run application equipped with male & female quick connect harnesses

Dimming: 5-wire 0-10V (100%-10%), cable kit with 5 wires power feed; + 0.4" 5-conductor

cable + 5" round canopy Voltage: 120-277V **Power Factor:** > .95

**THD:** < 20

Life: 50,000 hours L70

**Operating Temperature:** -4°F (-20°C) - 122°F (50°C)

Warranty: 1 year carefree for parts & components (labor not included)

Listings: CA Title 24 Compliant, cETL Listed, LED chips tested to LM-80 standards








## joined together in seamless runs of any length. **AVAILABLE LENGTHS**





## ORDERING INFORMATION Example: (12124-4-D48-MW-30K-WH-AC48-EM)

Model	Size   Wattage   Lumens	Colo	r Temp	Fi	nish	Mounting	Options
12124	4 Foot (48")  4-D48   Down: 48 watts   5900 Lumens    4-D57   Down: 57 watts   7000 Lumens    4-D24U12   Down: 24 watts   Up: 12 watts   3600 Lumens    4-D32U16   Down: 32 watts   Up: 16 watts   6470 Lumens    4-D60U30   Down: 60 watts   Up: 30 watts   10820 Lumens	30K 35K 40K 50K	3000K 3500K 4000K 5000K	WH BK RD IN SL	White Std Black Red Iron Silver	AC48 Std 48" Adjustable Cable AC96 96" Adjustable Cable	<b>EM</b> Emergency Battery Backup Remote

8 Foot (96")

8-D97	Down: 96 watts	11850 Lumer	ns				
8-D114	Down: 114 watts 14000 Lumens						
8-D48U24	Down: 48 watts	Up: 24 watts	9580 Lumens				
	Down: 64watts						
9-D120H60	Down: 120 watts	Up: 60 watts	21640 Lumei				