

ASSEMBLY AND INSTALLATION:

TURN OFF POWER FROM THE MAIN CIRCUIT BEFORE INSTALLING FIXTURE.

- Make sure power is completely off at the fuse box.
- Have your fixture installed by a qualified licensed electrician
- Prepare everything in a clear area.
- Wear gloves at all times during this installation.
- Read instructions carefully before you start assembly.
- Keep this instruction sheet for future reference.

Technical Support: 1-877-733-5236

Please Note:

- All Alcon Lighting LED fixtures come with pre-wired LED module(s).
- Unless instructed to do so, please do not touch any part of the LED module(s) as an unnecessary contact with the module could cause permanent damage.
- For dimming, an ELV (Electronic Low Voltage) type of dimmer is required.

1. Remove the fixture from its original packaging. Remove the mounting plate (**1d**) and anchor plate (**2a**) from within the canopy (**2c**) and attach the mounting plate (**1d**) to the electrical junction box (**1a**), using the two screws (**1c**) provided in the hardware package.
2. Attach the anchor plate (**2a**) to the mounting plate (**1d**), which is attached to the electrical junction box (**1a**) on the wall. First attach all wiring (**1b**) with the provided marrets (white to white "N", black to black "L", ground to ground "G"). Now connect the anchor plate (**2a**) to the mounting plate (**1d**) using the screws (**2b**) provided. Be sure to thread the screws through the threaded holes in the mounting plate. Now push the canopy backplate (**2c**) onto the anchor plate (**2a**). Using the set screws (**2d**) thread the canopy backplate to the anchor plate turning clockwise until secure.
3. You have now completed the installation of your fixture, please enjoy.

