

SHOP NOW >

FEATURES & SPECIFICATIONS

INTENDED USE


The **i44 Series Architectural Linear LED Suspension Lighting** fixtures bring clean lines and clear light to commercial LED or residential office lighting interiors. Our sleek, stylish fixtures offer highly effective and efficient lighting solutions for hotels, offices, retail outlets, restaurants, and more.

DETAILS

4 FT - W 4" x L 48" x H 4"
Construction: Die-formed and welded 22-gauge cold rolled steel
Lens: Snap In Frosted Acrylic
Mount: 48" Adjustable Aircraft Cable¹, 3 Wire Power feed/cable

ADDITIONAL FEATURES

Type: Direct Downlight
Voltage: 120V-277V
Wattage: 36W (2x18W)
Lumens: 4200 lms
CRI: 83
Life: 50,000 Hours
Listings: ETL and DLC for LED component only LED lamp included



Ordering Information:

Example: (12111-4-2W-35K-WH)

Model	Dimming	Color Temp	Finish	Options
12111-4 Pendant	Blank Non-Dimming <i>(Standard)</i>	35K 3500K 40K 4000K 50K 5000K	WH White BK Black SL Silver BR Bronze IR Iron	CRWK Continuous Row Wire Kit EM² Emergency Backup Battery DS² Integrated Daylight Sensor
	2W 2-Wire Incandescent Dimming <i>(120V only)</i> <i>(Title 24 Compliant)</i>			

¹White or Silver Finish Pendant shipped with a White Cable. Black Finish Pendant shipped with a Black Cable.
²Factory Installed