

FEATURES & SPECIFICATIONS

INTENDED USE

The i44 Series Architectural Linear LED

Suspension Lighting fixtures bring clean lines and clear light to commercial LED or residential office lighting interiors. Our sleek, stylish fixtures offer highly effective and efficient lighting solutions for hotels, offices, retail outlets, restaurants, and more.



8 FT - W 4" x L 96" x H 4"

Construction: Die-formed and welded

22-gauge cold rolled steel **Lens:** Snap In Frosted Acrylic

Mount: 48" Adjustable Aircraft Cable¹, 3 Wire

Power feed/cable

ADDITIONAL FEATURES

Type: Direct Downlight Voltage: 120V-277V Wattage: 72W (4x18W) Lumens: 8400 lms

CRI: 83


Life: 50,000 Hours


Listings: ETL and DLC for LED component only

LED lamp included









Ordering Information:

Example: (12111-8-2W-35K-WH-EM)

Model	Dimming	ning Color Temp		Finish		Options	
12111-8 Pendant	Blank Non-Dimming (Standard)	35K	3500K	WH	White	CRWK	Continuous Row Wire Kit
		40K	4000K	BK	Black	EM ²	Emergency Backup Battery
	2W	50K	5000K	SL	Silver	DS ²	
	2-Wire Incandescent Dimming			BR	Bronze		Integrated Daylight Sensor
	(120V only) (Title 24 Compliant)			IR	Iron		

¹White or Silver Finish Pendant shipped with a White Cable. Black Finish Pendant shipped with a Black Cable.